



BRC-
T9270D/9280D

品名：机电一体曲腕机
Direct-Drive Feed Off The Arm Machine

特性：适应范围广，节能高效
Wide range of application, power saving and high efficiency



节能高达71%
Power saving 71%



悬臂筒形设计，适用范围广
Cantilever tube design, wide range of application

技术参数 Specification

				 (mm)	 (mm)	 (mm)	A	M	H	 (S.p.m)	 (mm)	NW / GW (kg)
BRC-T9270D-12-Q	TV×64 12#	2	4	1/4,3/16	3.5	8	●			3500	685×535×475	56/60
BRC-T9270D-12-2PL-Q	TV×64 12#	2	4	1/4,3/16	3.5	8	●			3500	685×535×475	56/60
BRC-T9270D-12-2PS-Q	TV×64 12#	2	4	1/4,3/16	3.5	8	●			3500	685×535×475	56/60
BRC-T9270D-12-2PL-Q	TV×64 12#	2	4	3/16	4.2	8	●			3500	685×535×475	56/60
BRC-T9270D-13-Q	TV×64 12#	3	6	1/8	3.5	8	●			3500	685×535×475	56/60
BRC-T9270D-13-2PL-Q	TV×64 12#	3	6	1/8	3.5	8	●			3500	685×535×475	56/60
BRC-T9270D-22-Q	TV×64 14#	2	4	1/4,3/16	3.5	8		●		3500	685×535×475	56/60
BRC-T9270D-22-2PL-Q	TV×64 14#	2	4	3/16	3.5	8		●		3500	685×535×475	56/60
BRC-T9280D-53-Q	TV×5 21#	3	6	1/8	4.2	10			●	3500	685×535×475	56/60
BRC-T9280D-73-2PL-Q	TV×5 21#	3	6	1/8	4.2	10			●	3500	685×535×475	56/60
BRC-T9280D-73-PL-Q	TV×5 21#	3	6	1/8	4.2	10			●	3500	685×535×475	56/60
BRC-T9280D-73-PS-Q	TV×5 21#	3	6	1/8	4.2	10			●	3500	685×535×475	56/60

注 (Note) :
PL-简易后拖轮; PS-外置式后拖轮; BRC-T9270D-12-2PL-Q机型针距4.2mm为雨衣专用机。
PL : rear puller; PS : box puller; BRC-T9270D-12-2PL-Q needle gauge is 4.2mm: for sewing raincoats.