



X5

品名：全新直驱包缝机
Power Saving Overlock Machine

特性：性能稳、易操作、效率高
Easy operation, high efficiency



德国工艺，稳定耐用
German technology, stable and durable



出厂参数，一键复原
Factory reset

技术参数 Specification

													
					(mm)				(mm)	(S.p.m)	(mm)	NW /GW (kg)	
X5-2	接布缝 Fabric joint sewing	DC×27 11#	1	2	—	6	3.8	0.7-2	3.5	5500	525×360×510	28/36	
X5-02×250	包兜缝 Pocket double chain rolling stitch	DC×27 14#	2	4	5	5	3.8	0.7-2	3.5	5500	525×360×510	28/36	
X5-3-02/233	基本缝 Plain seaming	DC×27 11#	1	3	—	4	3.8	0.7-2	5	5500	525×360×510	28/36	
X5-3-82/233	倒回缝 Back latching stitch	DC×27 11#	1	3	—	4	3.8	0.7-2	5	5500	525×360×510	28/36	
X5-3-12/233	下摆缝 Bottom hemming	DC×27 11#	1	3	—	4	3.8	0.7-2	5	5500	525×360×510	28/36	
X5-3-32R2/223	密拷缝 Baby overlock stitch	DC×27 9#	1	3	—	1.5	3.8	0.7-2	5	5500	525×360×510	28/36	
X5-WF-3-02/213	无纺布 Non-woven fabric	DC×27 14#	1	3	—	4	8.5	—	5	5500	525×360×510	28/36	
X5-4-M03/333	基本缝 Plain seaming	DC×27 11#	2	4	2	4	4.6	0.7-2	5.5	5500	525×360×510	28/36	
X5-4-83/323	倒回缝 Back latching stitch	DC×27 11#	2	4	2	4	4.2	0.7-2	5.5	5500	525×360×510	28/36	
X5-4-M03/333/H/M	厚料 Heavy fabric	DC×27 11#	2	4	2	4	4.6	0.7-2	6	5500	525×360×510	28/36	
X5-MJ-4-53/233	毛巾缝 Towel ending	DC×27 11#	2	4	2	4	3.8	0.7-2	5	5500	525×360×510	28/36	
X5-5-53/233	包条缝 Strip attach seaming	DC×27 14#	2	5	3	4	3.8	0.7-2	5	5500	525×360×510	28/36	
X5-5-02A/233	薄料 Light fabric	DC×27 11#	2	5	3	4	3.8	0.7-2	5	5500	525×360×510	28/36	
X5-5-03/233	5×5线迹 5×5 stitch	DC×27 14#	2	5	5	5	3.8	0.7-2	5	5500	525×360×510	28/36	
X5-5-03/333	3×4线迹 3×4 stitch	DC×27 14#	2	5	3	4	3.8	0.7-2	5	5500	525×360×510	28/36	
X5-5-A04/435	极厚料 Extra heavy fabric	DC×27 19#	2	5	5	6	5	0.8-1.5	7	5500	525×360×510	28/36	
X5-6-03/333	基本缝 Plain seaming	DC×27 11#	3	6	3×2	4	3.8	0.7-2	5	5500	525×360×510	28/36	

注 (Note) :
H/M:厚薄适应性广。
H/M: wide range for light to heavy materials.