OVEROCK machine



820D



- * Built-in upper knife clutch device.
- * Built-in tesion abjusting device.
- * All knobs and lever are located at operator's left hand side.
- With differential and sitich length knobs.
- Built-in narrow rolled hemming. Not necessary to change the needle plate.
- * Built-in looper threader
- Detachable expansion plate for free arm sewing.
- * Built-in sewing lamp

Overlock machine



- · One needle 3 Threads overlock machine
- · Light weight Aluminum inner frame.
- Use needle HAx1 (# 80/90)
 or 130/705H (# 12/14)
- 1250 RPM Speed
- 1.1 4.0 mm stitch length.
- 1.5 -5.0 mm stitch width.
- Snap on presser foot.
- 25 mm needle bar stroke.
- N. Weight: 6.5Kgs / G. weight: 8.0 Kgs

5 pcs Optional feet



Built-in upper knife clutch device



Built-in tension adjusting device



Built-in sewing lamp



Auto looper threader



Differential and stitch length knobs



Tension release:
To ensure all 3 threads can be inserted in the discs. You can also remove the finished work piece without the interruption on tensions.



Built-in rolled hem: No need to change the needle plate



Free arm: Detachable extension plate for free arm sewing



Safety switch:
To prevent any danger
while looper cover is opened

