

Energy saving 节能

Stable 稳定

Direct-drive 直驱



DL7200B

DL7200B | SERIES DL7400 | SERIES

直 驱 单 针 平 缝 机

Direct-drive Single-needle Lockstitch Machine



DL7400

DL7200B SERIES

FEATURES



延续DL7200优异的车缝性能, 再新增特点
Following the excellent sewing performance of DL7200, and added the new features

1 新切线机构：超短切线线头(3mm)
传统的切线机构为一组固定刀与活动刀，新切线机构为双动刀设计，在最接近针板处，进行切线动作，达成超短线头效果
New trimming mechanism:
Very short trimmed thread end (3mm)
Traditional trimming mechanism is a pair of fixed knife and moving knife. The new trimming mechanism is a pair of dual-moving knives. Thread trimming is made at the point near the needle plate to have a very short trimmed thread end.

2 封闭式油盘
传统的油盘为开放式，DL7200A以封闭式设计，确保机油不飞溅
Sealed oil tank
Traditional oil tank is open type. DL7200A's oil tank is sealed type, which the oil will not come out from the machine.

3 新型操作面板
- 设定参数图示化，并有中英文提示，直觉式操作，不需查阅说明书
- 各项功能的快捷键：分区，动线设计良好
New control panel
- Parameters are shown by graphic with English and Chinese, which makes intuitive operation and no need to check manual book.
- Hot keys of the functions: layout and setting route are clear.

4 防鸟巢功能 (选配)
可避免起缝时，在底面的「鸟巢」现象，对于各种压明线的工序，例如标签车缝，可以提高车缝品质与效率
Bird nest prevention (optional)
The device avoids the "bird nest" problem on the bottom side, which happens at the sewing starting. Applicable to the sewing of top stitch e.g. label attaching, which improves the sewing quality and the efficiency.



规格 SPECIFICATIONS

DL7200B						功能选配 Function Option				
						代码 Function Code	倒缝 Reverse Feeding	电子夹线 Thread Nipper	抬压脚 Auto Lifter	防鸟巢 Bird nest prevention
DL7200B-BH1	0-6	15.5	手动 Ha nd 5.5	自动 Auto 10-13	#20~#23	3500	V	V	-	-
DL7200B-BM1	0-5	18			#11~#14	4000	V	V	V	-
							V	V	V	V